

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 412  
Print date: 26.12.2022  
Version: 8.1

SILAFIX Sperrgrund  
Revision date: 22.12.2022  
Issue date: 22.12.2022

EN  
Page 1 / 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. product identifiers

Article No. (manufacturer/supplier) 412  
Trade name/designation SILAFIX Sperrgrund  
farblos  
UFI: XQ8V-Q5KU-E99W-T6KY

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses:

Coating material to protecting surfaces

### 1.3. Details of the supplier of the safety data sheet

#### supplier (manufacturer/importer/downstream user/distributor)

Knuchel Farben AG  
Farben + Lacke Telephone: +41 (0) 32 636 50 40  
Steinackerweg 11 Telefax: +41 (0) 32 636 50 45  
CH-4537 Wiedlisbach

#### Department responsible for information:

laboratory Manager  
E-mail (competent person) info@knuchel.ch

### 1.4. Emergency telephone number

Emergency telephone number 145 (+41 (0)44 251 51 51)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### Hazard pictograms



Danger

#### Hazard statements

H225 Highly flammable liquid and vapour.  
H318 Causes serious eye damage.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P280 Wear protective gloves and eye/face protection.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER or doctor/ physician.  
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/container to industrial incineration plant.

#### Hazard components for labelling

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 412  
Print date: 26.12.2022  
Version: 8.1

SILAFIX Sperrgrund  
Revision date: 22.12.2022  
Issue date: 22.12.2022

EN  
Page 2 / 10

butan-1-ol

## Supplemental hazard information

not applicable

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**Description** solvent-based acrylic resin, containing the following hazardous substances:

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No. CAS No. Index No.	REACH No. Designation classification // Remark	weight-%
200-751-6 71-36-3 603-004-00-6	01-2119484630-38 butan-1-ol Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / STOT SE 3 H335 / STOT SE 3 H336 / Flam. Liq. 3 H226 Acute toxicity estimate (ATE), ATE (oral): 2292 mg/kg bw	1 - 5
201-159-0 78-93-3 606-002-00-3	01-2119457290-43 butanone Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066	1 - 5

#### Additional information

Full text of classification: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Unsuitable extinguishing media

strong water jet

### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 412  
Print date: 26.12.2022  
Version: 8.1

SILAFIX Sperrgrund  
Revision date: 22.12.2022  
Issue date: 22.12.2022

EN  
Page 3 / 10

## 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limit values:

butan-1-ol

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

WEL, STEL: 154 mg/m<sup>3</sup>; 50 ppm

Remark: (may be absorbed through the skin)

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 412  
Print date: 26.12.2022  
Version: 8.1

SILAFIX Sperrgrund  
Revision date: 22.12.2022  
Issue date: 22.12.2022

EN  
Page 4 / 10

WEL, TWA: 600 mg/m<sup>3</sup>; 200 ppm  
WEL, STEL: 899 mg/m<sup>3</sup>; 300 ppm

## Additional information

TWA : Long-term occupational exposure limit value  
STEL : short-term occupational exposure limit value  
Ceiling : peak limitation

## DNEL:

butan-1-ol

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

DNEL long-term oral (repeated), Workers: 3,125 mg/kg  
DNEL acute inhalative (local), Workers: 310 mg/m<sup>3</sup>  
DNEL acute inhalative (systemic), Workers: 310 mg/m<sup>3</sup>  
DNEL long-term inhalative (local), Workers: 310 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Workers: 310 mg/m<sup>3</sup>  
DNEL long-term oral (local): 3,125 mg/kg  
DNEL long-term inhalative (local), Consumer: 55 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Consumer: 55 mg/m<sup>3</sup>

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

DNEL long-term dermal (systemic), Workers: 1161 mg/kg bw/day  
DNEL long-term inhalative (systemic), Workers: 600 mg/m<sup>3</sup>  
DNEL long-term dermal (systemic), Consumer: 412 mg/kg bw/day  
DNEL long-term inhalative (systemic), Consumer: 106 mg/m<sup>3</sup>  
Long-term - oral, systemic effects, Consumer: 31 mg/kg bw/day

## PNEC:

butan-1-ol

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

PNEC aquatic, freshwater: 0,082 mg/L  
PNEC aquatic, marine water: 0,0082 mg/L  
PNEC aquatic, intermittent release: 2,25 mg/L  
PNEC sediment, freshwater: 0,178 mg/kg  
PNEC sediment, marine water: 0,0178 mg/kg  
PNEC, soil: 0,015 mg/kg  
PNEC sewage treatment plant (STP): 2476 mg/L

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

PNEC aquatic, freshwater: 55,8 mg/L  
PNEC aquatic, marine water: 55,8 mg/L  
PNEC aquatic, intermittent release: 55,8 mg/L  
PNEC sediment, freshwater: 284,7 mg/kg Sediment dry weight  
PNEC sediment, marine water: 284,7 mg/kg Sediment dry weight  
PNEC, soil: 22,5 mg/kg  
PNEC sewage treatment plant (STP): 709 mg/L  
PNEC Secondary Poisoning: 1000 mg/kg food  
oral

## 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

### Personal protection equipment

#### Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

#### Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 412  
Print date: 26.12.2022  
Version: 8.1

SILAFIX Sperrgrund  
Revision date: 22.12.2022  
Issue date: 22.12.2022

EN  
Page 5 / 10

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye/face protection

Wear closely fitting protective glasses in case of splashes.

#### Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	refer to label
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	78 °C Source: Ethanol
Flammability:	Highly flammable liquid and vapour.
Lower and upper explosion limit:	
Lower explosion limit:	3.23 Vol-%
Upper explosion limit:	15 Vol-% Source: Ethanol
Flash point:	12 °C Method: DIN 53213
Auto-ignition temperature:	360 °C Source: butan-1-ol
Decomposition temperature:	not applicable
pH at 20 °C:	not applicable
Cinematic viscosity (40°C):	< 80 mm <sup>2</sup> /s
Viscosity at 20 °C:	20 - 24 sec DIN 4 mm
Solubility(ies):	
Water solubility at 20 °C:	partially soluble
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	59 mbar Source: Ethanol
Density and/or relative density:	
Density at 20 °C:	0.84 g/cm <sup>3</sup>
Relative vapour density:	not applicable
particle characteristics:	not applicable
9.2. Other information	
Solid content:	10 weight-%
solvent content:	
Organic solvents:	85 weight-%
Water:	5 weight-%

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 412  
Print date: 26.12.2022  
Version: 8.1

SILAFIX Sperrgrund  
Revision date: 22.12.2022  
Issue date: 22.12.2022

EN  
Page 6 / 10

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

#### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

#### 10.5. Incompatible materials

not applicable

#### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

butan-1-ol

oral, LD50, Rat: 2292 mg/kg

Method: OECD 401

Harmful if swallowed.

dermal, LD50, Rabbit: 3430 mg/kg

Method: OECD 402

butanone

oral, LD50, Rat: 2193 mg/kg ; Evaluation Slightly toxic

Method: OECD 423

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

Slightly toxic

inhalative (vapours), LD50, Rat: 34,5 mg/L

##### Skin corrosion/irritation; Serious eye damage/eye irritation

Causes serious eye damage.

butan-1-ol

Skin, Rabbit (4 h)

Method: BASF - Test

eyes, Rabbit

butanone

Skin, Rabbit (4 h)

Method: OECD 404

May dry out the skin and cause discomfort and skin inflammation.

eyes, Rabbit

Method: OECD 405

##### Respiratory or skin sensitisation

butanone

Skin, Maximization test, Guinea pig: ; Evaluation not sensitising.

Method: OECD 406

Respiratory system, Maximization test, Guinea pig: ; Evaluation not sensitising.

Method: OECD 406

##### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

butan-1-ol

teratogenicity, oral

Method: NOAEL

Rat; 1.454 mg/kg; Toxicological effects in dams

teratogenicity, oral

Method: NOAEL

Rat; 5.654 mg/kg

teratogenicity, inhalative

Method: NOAEL

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 412  
Print date: 26.12.2022  
Version: 8.1

SILAFIX Sperrgrund  
Revision date: 22.12.2022  
Issue date: 22.12.2022

EN  
Page 7 / 10

Rat; 10.8 mg/l; Toxicological effects in dams  
teratogenicity, inhalative

Method: NOAEL

Rat; 24.7 mg/l

Reproductive toxicity, inhalative

Method: NOAEL

Rat; 18.5 mg/l; parents

Reproductive toxicity, inhalative

Method: NOAEL

Mouse; 18.5 mg/l; F1

butanone

Germ cell mutagenicity; Evaluation Not known as germ cell mutagen. Based on test data for the material. Test(s) equivalent or similar to OECD Guideline 471 473 474 476.

Carcinogenicity; Evaluation Not known to cause cancer.

Reproductive toxicity; Evaluation Is not known to be toxic to reproduction.

Based on test results for structurally similar substances. Test(s) equivalent or similar to OECD Guideline 414 416.

Lactation; Evaluation No harmful effect on infants known through breast milk.

## STOT-single exposure; STOT-repeated exposure

butanone

Specific target organ toxicity (repeated exposure)

Liver damage is possible.; Danger of serious damage to health by prolonged exposure.

## Aspiration hazard

butan-1-ol

Aspiration hazard

butanone

Aspiration hazard; Evaluation Inhalation of high vapour concentrations may cause symptoms such as headache, dizziness, fatigue, nausea and vomiting.

Chronic exposure may cause dermatitis. ; Irritating to eyes and respiratory system.

## Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

## Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

## 11.2. Information on other hazards

### Endocrine disrupting properties

No information available.

## SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

## 12.1. Toxicity

butan-1-ol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 1376 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1328 mg/L (48 h)

Method: OECD 202

Algae toxicity, EC50, Selenastrum capricornutum: 225 mg/L

Method: OECD 201

literature value

Bacteria toxicity, EC10, Pseudomonas putida: 2476 mg/L (17 h)

Method: DIN 38412

butanone

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 2993 mg/L (96 h)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 412  
Print date: 26.12.2022  
Version: 8.1

SILAFIX Sperrgrund  
Revision date: 22.12.2022  
Issue date: 22.12.2022

EN  
Page 8 / 10

Daphnia toxicity, EC50, Daphnia magna: 308 mg/L (48 h)  
Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 2029 mg/L (96 h)

## Long-term Ecotoxicity

butan-1-ol

Daphnia toxicity, NOEL, Daphnia magna (Big water flea): 4,1 mg/L (21 d)  
Method: OECD 211

## 12.2. Persistence and degradability

butan-1-ol

Biodegradation: 92 percent (20 d); Evaluation Readily biodegradable (according to OECD criteria) aerobic.; Activated sludge; Biochemical oxygen demand

butanone

Hydrolysis: Evaluation No significant transformation due to hydrolysis is expected.  
Photolysis: Evaluation Due to photolysis, no significant transformation is to be expected.  
Air oxidation: Evaluation Moderate degradation is to be expected in air.  
Biodegradation: 98 percent (28 d); Evaluation Readily biodegradable (according to OECD criteria).

## 12.3. Bioaccumulative potential

butan-1-ol

Partition coefficient: n-octanol/water:  
Bioaccumulation is not to be expected.  
Distribution coefficient n-octanol/water (log KOW): 0,88

## 12.4. Mobility in soil

butan-1-ol

Mobility in soil:  
The substance does not evaporate from the water surface into the atmosphere.; Does not adsorb to the ground.

butanone

:

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

#### List of proposed waste codes/waste designations in accordance with EWC

080111\* Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

#### Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

## SECTION 14: Transport information

### 14.1. UN number or ID number

UN 1263

### 14.2. UN proper shipping name

Land transport (ADR/RID): Paint  
Sea transport (IMDG): PAINT  
Air transport (ICAO-TI / IATA-DGR): Paint

### 14.3. Transport hazard class(es)



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 412  
Print date: 26.12.2022  
Version: 8.1

SILAFIX Sperrgrund  
Revision date: 22.12.2022  
Issue date: 22.12.2022

EN  
Page 9 / 10

3

#### 14.4. Packing group

II

#### 14.5. Environmental hazards

Land transport (ADR/RID) not applicable

Marine pollutant not applicable

#### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

##### Further information

##### **Land transport (ADR/RID)**

Tunnel restriction code D/E

##### **Sea transport (IMDG)**

EmS-No. F-E, S-E

#### 14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### **EU legislation**

##### **Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**

VOC-value (in g/L): 716

##### **National regulations**

##### **Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

#### 15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
200-751-6 71-36-3	butan-1-ol	01-2119484630-38
201-159-0 78-93-3	butanone	01-2119457290-43

### SECTION 16: Other information

##### **Full text of classification in section 3**

Acute Tox. 4 / H302

Acute toxicity (oral)

Harmful if swallowed.

Skin Irrit. 2 / H315

Skin corrosion/irritation

Causes skin irritation.

Eye Dam. 1 / H318

Serious eye damage/eye irritation

Causes serious eye damage.

STOT SE 3 / H335

STOT-single exposure

May cause respiratory irritation.

STOT SE 3 / H336

STOT-single exposure

May cause drowsiness or dizziness.

Flam. Liq. 3 / H226

Flammable liquids

Flammable liquid and vapour.

Flam. Liq. 2 / H225

Flammable liquids

Highly flammable liquid and vapour.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

##### **Classification procedure**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2

Flammable liquids

On basis of test data.

Eye Dam. 1

Serious eye damage/eye irritation

Calculation method.

##### **Abbreviations and acronyms**

ADR

European Agreement concerning the International Carriage of Dangerous Goods by Road

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 412  
Print date: 26.12.2022  
Version: 8.1

SILAFIX Sperrgrund  
Revision date: 22.12.2022  
Issue date: 22.12.2022

EN  
Page 10 / 10

---

OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

## Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.